

Profile ADLER-Salt Spreader ST-E

Safety for winter roads!

The ST-E Salt Spreader comes with a 120- or 200-litre plastic composite tank held in a sturdy frame. The tank is equipped as standard with an additional gear drive agitator, a water-tight hinged lid and a leak-free drain plug. Rotational speed and spread rate can be conveniently controlled from the driver's seat. The ST-E Salt Spreader is also fitted with a powerful 12 volt geared motor for the spreader plate. The working width is continuously adjustable from 1 to 6 m.

Attachment systems:

- Universal attachment system for fork lift trucks and yard and wheel loaders is height adjustable and features tilt function
- Kat. I/II three-point hitch
- Hitch triangle
- Pick-up
- Scharmüller / Rockinger hitch

Accessories:

conveniently adjusted from the driver's cab

via smartphone

- > Speed-dependent, GPS-based quantity control
- LED lighting set, 12/24 V, as per traffic regulations

| ADLER-Salt Spreader | | ST-E 120 | ST-E 200 |
|--|--------|---|------------------------------------|
| Tank capacity | Litres | 120 | 200 |
| Speed adjustment | | Variable | Variable |
| Spreader plate motor | | Geared motor with splash water protection | |
| Separate agitator (fitted as standard) | | Driven by geared motor | Driven by geared motor |
| Casing | | V2A/V4A stainless steel, 2.5 mm | V2A/V4A stainless steel, 2.5 mm |
| Weight without mount | kg | 48 | 56 |
| Area performance | m² | e.g. 60,000 m2 per hour 10 km/h | |



Salt spreader attached to a yard/wheel loader



Universal mount system, hinged



Salt Spreader with side panel support



With the optional GPS function you will now receive additionally free of charge our ADLER spreading manager with spreading proof



Developed by ADLER, the beater and agitator system prevents bridging in the road grit