

Full of drive ...

Auger E-series

- ▶ Compact design
- ▶ Low total height
- ▶ Highly efficient
- ▶ Maintenance-free usage
- ▶ Sturdy design
- ▶ Versatile in use

DEVELOPED &
PRODUCED IN
GERMANY

Profile

ADLER-Auger E-series

Powerful performance. The Auger Range for every carrier vehicle.

The ADLER-Auger E-series is equipped with powerful orbital engines, which are protected by a sturdy housing. The machine is operated using a simple-acting or double-acting hydraulic control circuit.

The augers are mounted directly using the quick hitch mechanism or forklift forks on yard loaders or smaller wheel loaders. In the case of mini-excavators, the quick hitch coupler or a bolt attachment are used to mount attachments.

The universal joint in the auger attachment ensures that drilling is always vertical - no matter how the carrier vehicle is positioned on the ground.

The auger drills are equipped with exchangeable heads and blades suitable for light to medium soil. The augers are also easy to change using a bolt fixing mechanism. You can also work with medium and heavy soil quickly and effectively using our heavy duty auger blades and heads.

Accessories:

- ▶ Attachment options:
Excavator attachment as quick coupler or universal attachment for wheel loader, telescopic loader and front loader
- ▶ Auger drill (standard / heavy duty) with the following ø: 100 mm, 150 mm, 200 mm, 250 mm, 300 mm, 350 mm, 400 mm, 450 mm, 500 mm, 600 mm
- ▶ Pressure relief valve

ADLER-Augers	E 50	E 100	E 165
Drive	Hydraulic		
Auger diameter mm	to 200	to 300	to 500
Required hydraulic pressure & volume	160 bar > 20 l/min	200 bar > 20 l/min	200 bar / > 30 l/min
Torque daNm	50	100	165
Pressure relief valve	on option		
Weight* kg	90	101	115

* Weight without mounting system



ADLER E 100 with Ø 250 auger



Universal joint and support bearing as standard



Transport rack for E series



ADLER auger with wheel loader attachment



Auger drills and different qualities in standard and heavy-duty design

