

Cleared ...

Snow Blade V-series

- ▶ Up to 65 or 90 cm high and 135 to 330 cm wide
- ▶ Two swivel-mounted folding wings
- ▶ Hydraulic side swivel mechanism
- ▶ Anti-icing spring flaps
- ▶ Edge protections
- ▶ High-quality primer & powder coating
- ▶ Adjustable support wheels



Profile ADLER-Snow Blade V-series

The Snow ADLER for next winter!

We equip the V-series with edge protections, anti-icing spring flaps (made of spring steel ø 10 mm) and high-quality, height-adjustable support wheels.

By the great variety of flexible hitch systems for communal tractors and yard loaders you can apply the V-series snow blades individually and in a number of ways in winter road maintenance. The integrated leveling system also ensures consistently effective clearance results.

If your carrier-vehicle does not have a second double-acting hydraulic control circuit, you can make the desired swivel adjustments of your snow blade by means of an electric switch valve, which is available on option.

Accessories:

- ▶ Reinforced, heavy-duty wheels
- ▶ Electric switch valve for swivel operation
- ▶ Side marker lights, LED, 12/24 V with reflective strips, left/right
- ▶ Holders for warning flags
- ▶ Warning flags, made of flexible and rounded material
- ▶ Customised colour as per RAL colour chart (standard: RAL 2002)
- ▶ Comfort control system: At the push of a button, you can adjust – in straight position – the wings from right/left to Y or V shape.

ADLER-Vario-Snow Blade V-series	135	150	180	210	240	270	300	330
Clearance widths in V, Y and diagonal position (at 30° angled position) cm	121	129	155	190	215	235	258	289
Blade height outside/inside mm	550/650	550/650	550/650	750/900	750/900	750/900	750/900	750/900
Wheels Ø/mm	180 x 50	180 x 50	180 x 50	200 x 80	200 x 80	200 x 80	200 x 80	200 x 80
Weight (without mount) kg	185	190	200	353	389	412	465	511



V-series attached to yard loader



Also available in working widths from 135 cm up to 330 cm



Electric switch valve with overload protection provided by two pressure relief valves and nitrogen bubble



Universal attachment with leveling system and parking stand



All possible clearance configurations in V, Y and diagonal position