



**... it'll sweep you  
off your feet!**

## Sweeper K 750

- *750 mm brush diameter*
- *2 heavy-duty wheels Ø 400 mm*
- *With overrun protection as standard feature*
- *Internal hydraulic motor*
- *Suspended sweeper roller*
- *Universal attachment system*
- *In-house production*



**Front and rear attachment possible**

**ADLER Arbeitsmaschinen GmbH & Co. KG**

An den Bahngleisen 28 · 48356 Nordwalde · Germany · Phone +49 (0) 25 73/97 999-0

## Profile

### ADLER-Sweeper K 750

#### A clean sweep with ADLER

Further highlights include the high-quality heavy-duty swivel castor, which enable the ADLER K 750 to ride over potholes, railway tracks and rough terrain without any difficulty. As optional extras, you can fit your machine with a large-capacity hopper, use side brushes to sweep curbs and gutters, or easily reduce dust levels during sweeping thanks to our water injection system.

#### Accessories:

- Large dirt collector incl. simple sweeping mode, incl. wear-resistant sweeping lip and heavy-duty wheels  $\varnothing$  400 mm x 100 mm
- Rotary side brushes for sweeping close to the edge – perfect for sweeping gutters
- Water injection system 240 l for dust control
- Flow control valve 1" for hydraulic fluid volumes > 90 l/min
- Hydraulic angling for flexible simple sweeping
- Attachment front plate, DIN 76060  
Size 3 or 5, including hydraulic cylinder and levelling system for optimum adjustment to ground surface
- Scraper Attachment KV-series
- Side marker lights, LED, 12/24 V
- Customised colour as per RAL colour chart (standard: RAL 2002)

ADLER-Sweeper K 750		210	240	270	300	330
Working width straight/angled	cm	210/198	240/228	270/257	300/285	330/313
Total width	cm	233	262	292	321	351
Brush diameter	mm	750	750	750	750	750
Required hydraulic pressure & volume		160 bar / >35 l/min.		160 bar / >40 l/min.		
Weight, including mount/hopper	kg	499/690	596/800	674/890	748/995	875/1,135
Hopper capacity	litres	390	450	500	555	610
Area performance	m <sup>2</sup> /h	16,800	19,200	21,600	24,000	26,400
For carrier vehicles with operating weight	t	3+	4+	5+	6+	6+



Optional rotary side brush and 240-l water tank



K 750 suitable for front and rear attachment



Simple sweeping mode and 750 mm brush diameter as standard features



K 750 with hopper and Scraper Attachment



Hydraulic hopper emptying system



Three large wheels 400 mm x 100 mm